Precautions for use of Compact Chip LED products

- (1) When adopting the product for mass production, please exchange formal specifications with us.
- (2) Do not reverse-engineer the product including disassemble or analyze without our approval.
- (3) The product is not in conformity to IATF16949 or intended to be used for invehicle application. The product is not designed or manufactured to be used for special application (e.g. trains, ships, airplanes, spaceships, submarine repeaters, atomic energy control systems, traffic equipment, combustion equipment, medical devices, and safety devices). We will not guarantee any application suitability for goods like those described above that require special quality and reliability. In cases where the product is used in special applications and it causes extensive property damage, threatens human life or damages the human body, we will not be held liable.
- (4) The specification and appearance of the product may change without notice for improvement, etc.
- (5) This technical information and data is provided for users as is, and we do not guarantee that it is free from errors or defect in technical information and data, or this technical information and data conform to special applications, or this technical information and data does not infringe any rights of the user or third parties other than the user, or any other contents (including changes in contents for improvement of the specification and appearance of the product) thereof.

CL-421 Series



2.8(L) × 1.35(W) ×1.0(H) mm

●絶対最大定格 Absolute Maximum Rating

(Ta 25℃)

Product code	Color variation	P*1 (mW)	Pd (mW)	IF (mA)	IFP (mA)	VR (V)	Top (℃)	Tst (℃)
	Red	140	50	20	100*2	4	-25~+80	-30~+85
CL-421C4	Green		140	30				
	Blue		130	30				

- *1 Pは同時点灯時の全許容損失を示します。/*2 IFPの条件はduty 1/10 、パルス幅0.1 msecです。
- *1 P means total value of power dissipation when both colors are on. / *2 Conditions for IFP are pulse of 1/10 duty and 0.1 msec width.

●電気的光学的特性 Electrical and Optical Characteristics

(Ta 25℃)

Product code		VF			λd	lv*		
	Color variation	IF (mA)	typ (V)	max (V)	typ (nm)	IF (mA)	min (mcd)	typ (mcd)
CL-421C4	Red	20	2.2	2.78	624	20	520	700
	Green	20	3.45	4.12	530	20	850	1,350
	Blue	20	3.2	3.81	470	20	250	400

* NIST規格に準拠 * Compliant with NIST standards

特徴 Features


1. 同一パッケージで3色発光

3 colors emitting from a single package

2. 側面発光

Side-lighting type

●外形寸法図 Outline drawing



Recommendable soldering pattern

(Top view)

1

②装数量:3,000個/1リール(φ180mm) Loaded quantity:3,000pcs./1 reel(φ180mm)

ntroduction

ا